

## 114/900 (Core)

Manual and Fixed

[Manual and Fixed Bollards List](#)

Automatic

High Security and Anti-Terrorist

Optional Extras



[114/900 \(Mid\)](#)



[114/900 \(Premier\)](#)



The ATG 114/900 is utilised where visibility may be an issue, the increased height brings the bollards to the attention of pedestrians and is often utilised where large crowds of people may pass through.

The 114/900 bollards are lift assisted as standard, this decreases the lifting weight of the bollards by up to 80%.

**Wall thickness:** 0.20"

**Optional Extras**

- Lift Assist
- Folding Handle
- Sold Secure Lock
- Security Caps
- Drainage Pumps

**Basic Installation Information**

Diameter of hole: 24" Square  
 Depth of hole: 50"

Insurance companies recommend 4.25 feet spacings between bollard centres, ATG Access works to this recommendation unless otherwise stated.

**Statistics**

<b>Height (inch)</b>	:	35.5
<b>Diameter (inch)</b>	:	4.5
<b>Lifting weight (kg)</b>	:	-
<b>Lifting weight with Lift Assist (kg)</b>	:	-

- Anti Ram-raid (deterrent)
- Anti Ram-raid (proven)
- ATM Protection (Deterrent)
- ATM Protection (Proven)
- Commercial
- Demarcation
- Entrance security
- Garage forecourt
- Gate Protection
- Impact tested
- Industrial
- Parking bay protection
- Parks
- Perimeter Security
- Residential
- Retail
- Roller Shutter protection
- Shop Front protection
- Stadia
- Urban Landscaping